
Our Product Introduction





Basic Information

. Place of Origin: China . Brand Name: Homei

CE, ROHS, SGS, TUV · Certification:

HM-VC01 Model Number:

Minimum Order Quantity:

Packaging Details: Carton Packing size:21*5*30cm

. Delivery Time: 5-8 work days

Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

1000 PCS . Supply Ability:



Product Specification

Voltage: AC90V-260V/50HZ

• Output: 3*10A

• Signal Interface: Digital DMX-512 (1990).

Power Supply: Three-phase Five-wire AC380V±10%

L515×W485×H145 Dimensions:

. Highlight: 1024pcs Lamps All In One Controller,

8CH All In One Controller, **TUV All In One Controller**



Product Description

6-way digital dimming silicon box for stage lighting stage effect equipment

Power supply: three-phase five-wire AC380V±10%, frequency 50Hz±5%.

Signal interface: digital DMX-512 (1990).

Rated power: 6 channels × 6KW. The maximum output power of each circuit can reach 8kW. Terminal input, 3*10A bakelite plug output

Functional features:

- 1. The core device of the silicon box, the thyristor chip, adopts original imported materials, and the performance is stable and
- 2. Good heat dissipation device and forced air cooling are combined with intelligent environmental protection control system.
- 3. The efficient anti-interference choke has strong anti-interference ability, low noise, and current rise time of 220us-450us.
- 4. Starting circuit setting, preheating value setting.
- 5. The dimming curve can be set to linear or switch state, the switch value is 50%, and when the input brightness value in the switch state is greater than or equal to 50%, the corresponding output circuit is fully output, otherwise there is no output. Dimensions (mm): L515×W485×H145, whole machine weight: 17.5K





Guangzhou Hongmei Stage Lighting Co., Ltd



0086 15920458549



Joanna@homeilight.com



@ discostagelight.com

2nd Floor, No.1 Industrial Street, Yanger Village, Huadu istrict, Guangzhou, China