# 300W Colorful LED Profile Spot Light Waterproof LED Ellipsoidal Stage Light

#### **Basic Information**

- Place of Origin:
- Brand Name:
  - Homei CE/SGS/RoHS
- Certification:
- Model Number:
- Minimum Order Quantity:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

Our Product Introduction

for more products please visit us on discostagelight.com

- 2 pieces carton/flightcase 5-7 working days
- MoneyGram, Western Union, T/T, paypal

Guangdong, China

HM-P300W

500 Piece/Pieces per Month



### **Product Specification**

• Color Temperature(CCT): 6000K (Daylight Alert)

10

90

1-Year

110-220v

- Lighting Solutions Service: One-to-one After-sale Service • Working Time (hours): 50000
  - Product Weight kg :
  - Type: Moving Head Lights
  - Input Voltage(V):
  - Lamp Luminous Flux(Im): 15000
  - CRI (Ra>):
  - Working Temperature(°C): -25 85
  - Working Lifetime(Hour): 50000
  - IP Rating: IP33
  - Emitting Color: Warm White
  - Application: Theater
  - LED . Light Source:
  - Warranty(Year):



#### More Images



300W Waterproof Colorful LED Profile Spot Leko Ellipsoidal Light For Stage Equipment Outdoor

# 300W Waterproof Colorful LED Profile Spot Leko Ellipsoidal Light For Stage Equipment Outdoor

## **Product Description**

Voltage	100-240v 50-60HZ
Power	300w
Channel	2/24CH
Control mode	DMX512/master-slave/sound/auto
Beam angle	19/26/36/50 degrees (optional)
Packing size	50*30*25cm
Gross weight	15kg

Input/Output: AC100-240V50-60HZ Power input: POWER CON power plug Signal input/output: 3P-XLP input/output, DMX512 signal Power consumption power: maximum 200W Ultra-high brightness 200W, COB integrated light source LED white light Color temperature: 3200/5600K Control: 9DMX channels, LCD display, 4 dimming curves Selectable, master-slave synchronization, separate Beam angle: 19/26/36/50 degrees (optional) Refresh rate: 2000HZ Heat dissipation treatment: copper tube heat conduction + silent fan Housing Material: Engineered UBS Plastic Protection class: IP20 Working temperature: LED center temperature > 40 degrees Package size: 62× 25.5× 25.5CM Net weight: 5.75KG Gross weight: 6.6KG



