



## New 10\*60W Led Beam+Zoom Pixel Effect With Backlight Led Moving Head

Our Product Introduction

for more products please visit us on [discostagelight.com](http://discostagelight.com)

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Homei
- Certification: CE,SGS,TUV,Rohs
- Model Number: HM-L1060
- Minimum Order Quantity: 2 pieces
- Packaging Details: Carton/Flight Case
- Delivery Time: 7 working days
- Payment Terms: Western Union, T/T,PayPal



### Product Specification

- White Light Color Temperature: 6300K
- Luminous Flux: 22400 Lm
- LED Expected Lifespan: 20000 Hours
- Beam Angle: 2.8 ° -31 °
- Spot Angle: 5 ° -46 °
- Control Panel: LCD Display Screen
- Control Protocol: DMX512, RDM
- Power: 800 W
- Power Socke: Power Connector Input/output
- Highlight: 10\*60W Led Beam Moving Head, Backlight Led Beam Moving Head, Pixel Effect Led Beam Moving Head



### More Images



**Product Description****New 10\*60W Led Beam+Zoom Pixel Effect With Backlight Led Moving Head****Product Description**

Strobe end	96 x 3W CW LED 96 x 3W WW LED 96 x 0.5W RGB LED
White light color temperature	6300K
Luminous flux	22400 lm
LED expected lifespan	20000 hours
Beam angle	2.8 ° -31 °
Spot angle	5 ° -46 °
Control panel	LCD display screen
Control protocol	DMX512, RDM
Channel mode	17/27/99/108/168/8+100/8+160/170 channels
Software upgrade	updating software through a DMA connection
Power	800 W
Power socket	power connector input/output

Light source:

Beam end:

10 x 60W RGBW LED

Strobe end:

96 x 3W CW LED

96 x 3W WW LED

96 x 0.5W RGB LED

White light color temperature: 6300K

Luminous flux: 22400 lm

LED expected lifespan: 20000 hours

optical system

Zoom angle:

Beam angle: 2.8 ° -31 ° (beam end)

Spot angle: 5 ° -46 ° (beam end)

Control and Program

5 buttons

Control panel: LCD display screen

Control protocol: DMX512, RDM

DMA channel modes: 7 types

Channel mode: 17/27/99/108/168/8+100/8+160/170 channels

Software upgrade: updating software through a DMA connection

Y-axis

Y-axis operating angle: 202 °

Electrical and Interface

Input power supply: 180-240V~50/60Hz

Power: 800 W

Power socket: power connector input/output

Signal input/output: Three core or five core XLR socket, RJ45

Lamp specifications

Lamp size:

Length: 1000 mm (39.4 ")

Width: 290 mm (11.4 ")

Height: 120 mm (4.7 ")



